

## URL-Referenzierungen tot he ZDB catalogue

The ZDB catalogue offers two kinds of views that can be linked to: the view of a hit list (`/list.xhtml`) and the „Detailed tilte record information“ (`/title.xhtml`).

There are several approaches to build an URL depending on the data (ZDB-ID, IDN, ISSN, ISIL) used for linking and with regard to the view (view of a hit list or view of „Detailed title record information“).

**Please note:** Please do not use quotes in context with ZDB-ID, IDN, ISSN und ISIL in a URL. This will possibly cause errors.

### 1. Linking to a specific title via ZDB-ID

It is best to use the permalink:

**Syntax:** `ld.zdb-services.de/resource/{ZDB-ID}`

**Example:** `ld.zdb-services.de/resource/1213-0`

The request will be forwarded to the ZDB catalogue. The usage of the permalink has the advantage of durability. Your link will work perfectly, even if the URL-syntax in the ZDB catalogue changes.

Alternatively you can use the parameter 'zdbid':

**Syntax:** `zdb-katalog.de/title.xhtml?zdbid={ZDB-ID}`

**Example:** `zdb-katalog.de/title.xhtml?zdbid=1213-0`

The request via ZDB-ID will be changed to a request via IDN automatically.

### 2. Linking to a specific title via IDN

**Syntax:** `zdb-katalog.de/title.xhtml?idn={IDN}`

**Example:** `zdb-katalog.de/title.xhtml?idn=010014071`

### 3. Additional options for linking via IDN and ZDB-ID

The basic URLs

`https://zdb-katalog.de/title.xhtml?zdbid={ZDB-ID}`

`https://zdb-katalog.de/title.xhtml?idn={IDN}`

may be extended by one or more parameters:

### 3.1 Selection of tabs in the „Detailed title record information“

**Syntax:** <Basis-URL>&tab={Number of tab referencing}

Name of the tab	Number of tab referencing
Holdings	0 (default)
Holdings overview	1
Holdings map	2
Title history	3
Title relations	4

**Examples:**

<https://zdb-katalog.de/title.xhtml?zdbid=287-2&tab=3>

<https://zdb-katalog.de/title.xhtml?idn=010002375&tab=2>

### 3.2 Sorting the holdings

**Syntax:** <Basis-URL>&sort={Sort key}

Sorting	Sort key
Name	(default)
ISIL	isil_sort
Interlibrary Loan Region	lvr_sort (<small L>vr_sort)

**Examples:**

[https://zdb-katalog.de/title.xhtml?zdbid=287-2&sort=lvr\\_sort](https://zdb-katalog.de/title.xhtml?zdbid=287-2&sort=lvr_sort)

[https://zdb-katalog.de/title.xhtml?idn=010002375&sort=isil\\_sort](https://zdb-katalog.de/title.xhtml?idn=010002375&sort=isil_sort)

### 3.3 Activation of a holdings filter

**Syntax:** <Basis-URL>&{Facet key}={facet attribute}

Filter	{Facet key}={Facet attribute}
Year of publication	vol=1988 (vo<small L>)
Interlibrary loan region	lvr=BAW (<small L>vr)
Location of library	ins=Ulm

**Examples:**

<https://zdb-katalog.de/title.xhtml?zdbid=287-2&tab=3&ins=Ulm>

[https://zdb-katalog.de/title.xhtml?idn=010002375&sort=isil\\_sort&vol=1988](https://zdb-katalog.de/title.xhtml?idn=010002375&sort=isil_sort&vol=1988)

#### 4 Expanded holdings in the „Holdings“-tab

**Syntax:** <Basis-URL> #{ISIL}

**Examples:**

<https://zdb-katalog.de/title.xhtml?zdbid=287-2#DE-82>

<https://zdb-katalog.de/title.xhtml?idn=010002375#DE-82;DE-37>

#### 5. Linking to a specific title via ISSN

Because an ISSN may be related to multiple title records, referencing via ISSN will only work in context with a hit list ([/list.xhtml](#)).

**Syntax:** [zdb-katalog.de/list.xhtml?t={ISSN}&key=iss](https://zdb-katalog.de/list.xhtml?t={ISSN}&key=iss)

**Example:** [zdb-katalog.de/list.xhtml?t=0006-3053&key=iss](https://zdb-katalog.de/list.xhtml?t=0006-3053&key=iss)

To reduce the hit list you can add parameters e.g. „**frm**“ (media type), „**yf**“ (first year of publication), „**yt**“ (last year of publication) and „**dok**“ (document type). Appropriate codes can be looked up in the following tables:

##### Reducing the media type by **frm**={Code}

Media type	Code
online edition	O
print edition	A
CD/DVD	S
microform	E
map	kt
sheet music	nt
sound carrier - speech	tt
sound carrier - music	mt
video	vi
braille	C

**Reducing the document type by dok={Code}**

Document type	Code
newspaper	Zeitung
journal	Zeitschrift
serial	Serie

**Example:** [zdb-katalog.de/list.xhtml?t=0006-3053&key=iss&frm=O](http://zdb-katalog.de/list.xhtml?t=0006-3053&key=iss&frm=O)

**6. Linking to a library's specific title via ISIL**

Using the jump label „#“, you can link directly to the holdings information of a specific library according to a specific title.

**Syntax:** [zdb-katalog.de/title.xhtml?zdbid={ZDB-ID}#{ISIL}\[;{ISIL}\]...](http://zdb-katalog.de/title.xhtml?zdbid={ZDB-ID}#{ISIL}[;{ISIL}]...)

**Example with one ISIL:** [zdb-katalog.de/title.xhtml?zdbid=1213-0#DE-22](http://zdb-katalog.de/title.xhtml?zdbid=1213-0#DE-22)

**Example with multiple ISILs:** [zdb-katalog.de/title.xhtml?zdbid=1213-0#DE-22;DE-703](http://zdb-katalog.de/title.xhtml?zdbid=1213-0#DE-22;DE-703)

Instead of the parameter ZDB-ID you can use other parameters (e.g. IDN, ISSN) for referencing the title.

**7. Referencing holdings of all libraries that have a specific volume recorded**

**Syntax:** [zdb-katalog.de/title.xhtml?zdbid={ZDB-ID}&vol={year of publication}](http://zdb-katalog.de/title.xhtml?zdbid={ZDB-ID}&vol={year of publication})

**Example:** [zdb-katalog.de/title.xhtml?zdbid=1213-0&vol=1992](http://zdb-katalog.de/title.xhtml?zdbid=1213-0&vol=1992)